

www.sumiteknatraj.com



ACTIVE PRO

Toggle Injection Moulding Machines

80 TO 600 TON

We believe that *Excellence* is a journey not a *Destination*





Shape Business Through Moulding

ABOUT US

SUMITEK NATRAJ MACHINERY PRIVATE LIMITED is Leading manufacturer of Plastic Injection Moulding Machines Established in the year 1976, we have achieved great feats in the field. We are known for our dynamism towards the technological advancements and for the outstanding customer service in the industry. In view of environmental concerns all over world, we continue to use latest technology to ensure our products remain energy efficient.

We have modular product range of various injection moulding machines consisting of **ACTIVE, SERVO GREEN, PETLINE, PVC STREAM SERVO, CPVC STREAM SERVO, ACCUFAST, SPAR, WAVE** ranging from 800 kn to 6000 kn clamping force, with modular injection Units 270 to 4800 to meet customer's specific needs.

With expertise of more than 40 years in manufacturing of PIMMS, we have always been preachers and executors of MAKE IN INDIA. The SUMITEK NATRAJ brand is synonymous with great RELIABILITY, high PRECISION and QUALITY having applications for automotive engineering, electrical parts, house hold, pharmaceuticals, packaging and beverage industries etc.

Recognized as one of the world's most trusted and innovative manufacturer of plastic injection moulding machines (PIMMs) by providing our customers highest quality products that combine performance and advanced technology with value pricing.

VISION

Continue to offer quality products to meet customer's needs beyond their expectations.



OUR FOCUS

- *Customer's Satisfaction
- *Quality Products



ACTIVE

80 TO 600 TON

SERIES MACHINES ARE SUITABLE FOR A WIDE VARIETY OF APPLICATIONS

APPLICATIONS

THIN WALL CONTAINER



HOUSEHOLD & CLEANING APPLIANCES



ELECTRICAL PRODUCTS



TOYS




IRRIGATION PRODUCTS




CAP & CLOSURES





CLAMPING UNIT

- Heavy Duty 5-point Double Toggle Mechanism With Large Mould Opening Stroke.
- High Stiffness Platen Design With Large Mould Mounting Area.
- Platen Casting Design With Finite Element Analysis For Maximum Rigidity.
- Mould Platen With T-slots (140 Ton & Above).
- Long Life By Providing Oil Less Bushing With Graphite Impregnated For Toggle Mechanism.
- Platens With Euromap Standard.
- Long Moving Platen Guide Increases Mould Life.




SKATE PAD

- High Wear Resistant Skate-pad For Heavy Mould Loading That Reduces Platen Deflection and Enhances Tiebar Life.
- High Wear Resistant Carbon Steel Strip.



AUTOMATIC GREASE LUBRICATION

- High Pressure Grease Lubrication System Provides Positive Lubrication.
- Ensures Continuous And Optimum Lubrication To Reduce Friction & Longer Toggle Life.




ENERGY EFFICIENT HYDRAULIC

- Return Line Filter With Clogging Sensor.
- High Efficiency & Fast Response Hydraulic Valve With Applicable Pipe Size Selection Reduces Oil Heat & Saves Power.
- Hydraulic Directional Valve With On /off Indicator Connector.




NUT GEAR

- High Wear Resistant & High Strength Gear Nut (tiebar Nut) That Gives Rigid & Positive Clamping Force.
- Friction Free Easy Moving Mould Height.




EJECTOR

- Smooth & Fast Ejection.
- Multiple Ejection Point & Evenly Distributed Ejection Force.
- Euromap Ejection Point.
- Easy Accessibility.





WIPER SEAL

- Keep Lubrication between Platen Hole & Tiebar For Smooth Movement.
- Dust Free Moving Platen Movement Gives Better Tiebar Life



INJECTION UNIT

- High Torque Hydraulic Motor For Better Plasticization.
- Longer Life Of Mould With Dual Nozzle Cylinder Design
- Provision For Multiple Screw Change By Changing Spline Bush Only.
- Low Noise Hydraulic Motor.
- Carriage Loaded Injection to Prevent Material Leakage



ELECTRICAL PANEL

- High Quality Electrical Components And Excellent Circuit Hardware Design.
- Stable And Reliable Control System With A Stronger Anti-interference Function.
- Ease In Maintenance.
- Over Voltage, Under Voltage Phase Loss And Phase Sequence Protection.
- Separate And Spacious Power & Control Wiring.
- 230 VAC Components Safe By Isolation Transformer.
- Ensured Panel Safety with IP-54 Protection.



HMI

- 8.0 TFT Colour Display, (10.4 Inch Optional)
- Precise Mould Safety.
- High Speed Microprocessor Controller.
- Self Diagnostics & Fault Finding Capacity.
- Graphical Presentation Of Important Functions.
- Automatic Calibration Of Sensors And Valves.
- PDP & SPC Function.
- Multiple User Passwords.
- Quality Data Logging.
- Unlimited Mould Data Storage Through USB
- USB Connection For Printer, Modem, USB Stick etc.

ANTI VIBRATING PAD

- Minimum Vibrations.
- Precise & Fast Leveling.
- No Civil Foundation Required.



SCREW & BARREL

- Gas Nitrided Injection Screw & Barrel For The Ultimate In Wear Resistance.
- Process Ability At Lower Melting Temperature.
- Excellent Homogeneous Melting.
- Special Screw Design.
- Improved Product Quality.
- Better Plastification Rate.




INDUCTION MOTOR WITH VARIABLE DISPLACEMENT PUMP

- Outstanding Power Saver.
- Precise And Fast Response.
- Outstanding Consistency And Repeatability.
- Low Noise Level.
- Lower Oil Heat Generation.
- Faster Response Towards Hydraulic System.
- Enhanced Oil & Hydraulic Seal's Life.
- Less Cooling Water Consumption.

Model	INJECTION UNIT	080 Ton			100 Ton			140 Ton			180 Ton			200 Ton																							
		270			270			410			590			1050																							
		AA	A	B	AA	A	B	AA	A	B	AA	A	B	AA	A	B	AA	A	B																		
INJECTION CAPACITY MAX. (GPPS)	gm	130	165	200	130	165	200	190	240	300	130	165	200	190	240	300	260	330	410	190	240	300	260	330	410	445	540	640	190	240	300	260	330	410	445	540	640
INJECTION PRESSURE	bar	2279	1800	1458	2279	1800	1458	2351	1904	1505	2279	1800	1458	2351	1904	1505	2476	1957	1585	2351	1904	1505	2476	1957	1585	2126	1757	1476	2351	1904	1505	2476	1957	1585	2126	1757	1476
INJECTION RATE	cc/sec	62	80	98	76	96	120	74	92	115	95	120	149	92	114	145	109	138	171	115	142	180	140	178	220	164	198	236	148	173	231	140	178	220	182	220	262
INJECTION SCREW STROKE	mm	170	170	170	170	170	170	200	200	200	170	170	170	200	200	200	220	220	220	200	200	200	220	220	220	240	240	240	200	200	200	220	220	220	240	240	240
SCREW DIAMETER	mm	32	36	40	32	36	40	36	40	45	32	36	40	36	40	45	40	45	50	36	40	45	40	45	50	50	55	60	36	40	45	40	45	50	50	55	60
SCREW L / D RATIO	-	24.8	22	19.8	24.8	22	19.8	24.5	22	19.6	24.8	22	19.8	24.5	22	19.6	24.8	22	19.8	24.5	22	19.6	24.8	22	19.8	23	21	19.2	24.5	22	19.6	24.8	22	19.8	23	21	19.2
SCREW SPEED	rpm	300	300	300	300	300	300	200	200	200	300	300	300	300	300	300	240	240	240	300	300	300	240	240	240	170	170	170	300	300	300	240	240	240	200	200	200
NO. OF HEATING ZONES (BARREL+NOZZLE)	-	3 + 1N			3 + 1N			3 + 1N			3 + 1N			3 + 1N			4 + 1N			3 + 1N			4 + 1N			4 + 1N			3 + 1N			4 + 1N			4 + 1N		
TOTAL HEAT CAPACITY	kw	10.2			10.2			11.8			10.2			11.8			14.1			11.8			14.1			18.1			11.8			14.1			18.1		
CLAMP UNIT																																					
CLAMP FORCE	ton	80			100			140			180			200			200			200			200			200			200			200			200		
CLAMP STROKE	mm	300			320			360			450			475			475			475			475			475			475			475			475		
MAXIMUM DAYLIGHT	mm	650			720			830			1000			1075			1075			1075			1075			1075			1075			1075			1075		
MINIMUM MOULD HEIGHT	mm	125			150			150			200			200			200			200			200			200			200			200			200		
MAXIMUM MOULD HEIGHT	mm	350			400			470			550			600			600			600			600			600			600			600			600		
PLATEN SIZE (H x V)	mm	535 x 550			590 x 605			670 x 670			785 x 755			822 x 765			822 x 765			822 x 765			822 x 765			822 x 765			822 x 765			822 x 765			822 x 765		
DISTANCE BETWEEN TIE ROD (H x V)	mm	360 x 360			400 x 400			445 x 445			540 x 505			570 x 500			570 x 500			570 x 500			570 x 500			570 x 500			570 x 500			570 x 500			570 x 500		
EJECTOR STROKE	mm	100			100			120			140			160			160			160			160			160			160			160			160		
EJECTOR FORCE	ton	3.3			5.3			5.3			5.3			7.5			7.5			7.5			7.5			7.5			7.5			7.5			7.5		
MOULD WEIGHT CAPACITY	kg	400			650			1000			1300			1500			1500			1500			1500			1500			1500			1500			1500		
GENERAL																																					
PUMP DRIVE	kw	7.5			9.4			11.2			11.2			11.2			15			15			18.7			18.7			22.5			22.5			30		
TOTAL OIL TANK CAPACITY	ltr	210			260			260			315			315			315			400			400			400			440			440			440		
CONNECTED LOAD	kw	17.7			17.7			23			23			29.5			29.5			30			33			37			34.5			37			48.5		
MACHINE DIMENSIONS (L x W x H)	m	4 x 1.5 x 2			4.5 x 1.5 x 2			4.5 x 1.5 x 2			5 x 1.6 x 2.1			5 x 1.6 x 2.1			5.2 x 1.6 x 2.1			5.5 x 1.7 x 2.2			5.5 x 1.7 x 2.2			5.8 x 1.7 x 2.2			5.9 x 1.9 x 2.3			5.9 x 1.9 x 2.3			6.2 x 1.9 x 2.3		
MACHINE WEIGHT (Approx.)	ton	3.6			4.2			4.4			5.1			5.3			5.8			7.0			7.2			7.5			7.6			7.8			8.1		


Model	INJECTION UNIT	UNIT	280 Ton			360 Ton			480 Ton			600 Ton																																																	
			1050			1430			1860			2090			3220			4800																																											
			AA	A	B	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C																																						
INJECTION CAPACITY MAX. (GPPS)	gm	445	540	640	740	870	1000	1000	1160	1335	740	870	1000	1000	1160	1335	1310	1500	1710	1310	1500	1710	1900	2400	2965	1900	2400	2965	3700	4488	5340																														
INJECTION PRESSURE	bar	2126	1757	1476	1750	1491	1286	1665	1436	1251	1750	1491	1286	1665	1436	1251	1615	1407	1236	1615	1407	1236	1695	1339	1085	1695	1339	1085	1940	1600	1350																														
INJECTION RATE	cc/sec	227	275	328	276	221	376	290	337	387	276	324	376	352	377	433	335	385	438	383	440	501	388	491	607	411	520	643	578	700	833																														
INJECTION SCREW STROKE	mm	240	240	240	280	280	280	320	320	320	280	280	280	320	320	320	360	360	360	360	360	360	400	400	400	400	400	400	500	500	500																														
SCREW DIAMETER	mm	50	55	60	60	65	70	65	70	75	60	65	70	65	70	75	70	75	80	70	75	80	80	90	100	80	90	100	100	110	120																														
SCREW L / D RATIO	-	23	21	19.2	22	20.3	21.5	22	20.5	22	22	20.3	21.5	22	20.5	22	22	20.5	22	22	20.5	22	24	21.25	22	24	21.5	22	23	22	22																														
SCREW SPEED	rpm	200	200	200	170	170	170	150	150	150	200	200	200	170	170	170	150	150	150	170	170	170	150	150	150	150	150	150	140	140	140																														
NO. OF HEATING ZONES (BARREL+NOZZLE)	-	4 + 1N			4 + 1N			4 + 1N			4 + 1N			4 + 1N			4 + 1N			4 + 1N			4 + 1N			4 + 1N			4 + 1N			4 + 1N																													
TOTAL HEAT CAPACITY	kw	18.1			22.5			25.7			27			31.2			22.5			25.7			27			31.2			32			36.6			32			36.6			40			45.8			40			45.8			54			57			62		
CLAMP UNIT																																																													
CLAMP FORCE	ton	280			360			480			600			600			600			600			600			600			600			600			600			600																							
CLAMP STROKE	mm	580			680			830			950			950			950			950			950			950			950			950			950			950																							
MAXIMUM DAYLIGHT	mm	1280			1510			1725			2020			2020			2020			2020			2020			2020			2020			2020			2020			2020																							
MINIMUM MOULD HEIGHT	mm	200			200			200			200			200			200			200			200			200			200			200			200			200																							
MAXIMUM MOULD HEIGHT	mm	700			830			900			1070			1070			1070			1070			1070			1070			1070			1070			1070			1070																							
PLATEN SIZE (H x V)	mm	900 x 895			1035 x 1035			1210 x 1180			1350 x 1355			1350 x 1355			1350 x 1355			1350 x 1355			1350 x 1355			1350 x 1355			1350 x 1355			1350 x 1355			1350 x 1355			1350 x 1355																							
DISTANCE BETWEEN TIE ROD (H x V)	mm	650 x 600			720 x 680			830 x 770			980 x 880			980 x 880			980 x 880			980 x 880			980 x 880			980 x 880			980 x 880			980 x 880			980 x 880																										
EJECTOR STROKE	mm	160			200			225			225			225			225			225			225			225			225			225			225																										
EJECTOR FORCE	ton	8.5			8.5			10.8			13.3			13.3			13.3			13.3			13.3			13.3			13.3			13.3			13.3																										
MOULD WEIGHT CAPACITY	kg	2700			4000			5500			7000			7000			7000			7000			7000			7000			7000			7000			7000																										
GENERAL																																																													
PUMP DRIVE	kw	30			37.5			37.5			37.5			37.5			45			48.5			48.5			52.5			60			60			60																										
TOTAL OIL TANK CAPACITY	ltr	510			660			660			660			660			850			850			850			850			950			950			950																										
CONNECTED LOAD	kw	48.5			60			63.5			64.5			69			77			81.5			80.5			85.5			88.5			94.5			92.5			98.5			114			117			122														
MACHINE DIMENSIONS (L x W x H)	m	6.5 x 1.9 x 2.4			6.5 x 1.9 x 2.4			6.8 x 1.9 x 2.4			7 x 2.1 x 2.5			7 x 2.1 x 2.5			7.5 x 2.3 x 2.7			8.5 x 2.3 x 2.6			8.5 x 2.3 x 2.6			8.5 x 2.3 x 2.6			8.5 x 2.3 x 2.6			9.5 x 2.3 x 2.6			9.5 x 2.3 x 2.6																										
MACHINE WEIGHT (Approx.)	ton	11.3			12			12.4			14.4			15			15.7			22.2			23.2			29			30.5			30.5			30.5																										

• Injection unit change is possible as per requirements.
• Actual figures may change depending on your final machine configuration.




80 Ton Moving Plate

Stationary Platen : Locating Ring Ø125 (±0.10 TO ±0.20)




100 Ton Moving Plate

Stationary Platen : Locating Ring Ø125 (±0.10 TO ±0.20)




200 Ton Moving Plate

Stationary Platen : Locating Ring Ø160 (±0.10 TO ±0.20)



280 Ton Moving Plate

Stationary Platen : Locating Ring Ø160 (±0.10 TO ±0.20)




600 Ton Moving Plate

Stationary Platen : Locating Ring Ø250 (±0.10 TO ±0.20)


T-SLOT DETAIL OF STATIONARY PLATEN & MOVING PLATEN

MACHINE	T- SOLT			
	A	B	C	D
80 TON	-	-	-	
100 TON				
140 TON	18	32	14	36
180 TON	18	32	14	36
200 TON	22	40	18	45
280 TON	22	40	18	45
360 TON	22	40	18	45
480 TON	22	40	18	45
600 TON	22	40	18	45




Detail - A

NOTE : ALL DIMENSIONS ARE IN MM.
T- SLOT & THREAD DIMENSIONS ARE AS PER EURO MAP STANDARD.
EJECT. CENTER DIST. ARE TYPICAL IN FOUR QUADRANTS




140 Ton Moving Plate

Stationary Platen : Locating Ring Ø125 (±0.10 TO ±0.20)




180 Ton Moving Plate

Stationary Platen : Locating Ring Ø125 (±0.10 TO ±0.20)



360 Ton Moving Plate

Stationary Platen : Locating Ring Ø160 (±0.10 TO ±0.20)



480 Ton Moving Plate

Stationary Platen : Locating Ring Ø200 (±0.10 TO ±0.20)

PLASTIC MATERIALS CHARACTERISTICS

MATERIAL	DENSITY gm/cc	PROCESSING TEMPERATURE (C°)	CLARITY T/O/C	kg/cm2 TENSILE STRENGTH AT YEILD	ELONGATION AT BREAK %	SOFTENING TEMPRATURE VICAT 0° C	HEAT DEFLECTION 0° C AT 66 PSI
LDPE	0.92	160-210	Translucent	95	200	85	50
LLDPE	0.92	180-260	Translucent	100	100	80	45
HDPE	0.96	190-280	T-O	250	500	126	75
PP Copolymer	0.90	190-300	T-C	290	500	150	90
PP Homopolymer	0.90	190-300	Translucent	310	200	152	96
PS (GPPS)	1.05	180-220	Clear	420	5	102	85
HIPS	1.05	180-220	T-O	275	45	88	83
ABS	1.05	210-270	Opaque	440	20	95	86
SAN	1.04	220-270	Clear	650	4	107	95
Polycarbonate (PC)	1.2	260-310	Clear	680	150	150	144
Nylon-6	1.13	240-270	T-O	740	40	215	165
Nylon-66	1.13	270-300	T-O	1240	300	245	238
RPVC	1.45	150-210	Clear	440	20	-	76
Acrylics	1.19	200-260	Clear	700	3	89	90
PBT	1.31	220-260	Opaque	530	300	172	155
Polyurethane	1.20	185-240	Clear	520	510	116	-
Acetal	1.41	180-240	Opaque	700	55	-	172
TPE	1.2	180-240	Opaque	310	375	195	111
PET	1.38	260-310	Clear	880	70	110	85

CLAMPING UNIT

Heavy duty 5-point double toggle mechanism with large mould opening stroke.
 High stiffness platen design with large mould mounting area.
 High wear resistance & high strength gear nut (tiebar nut) gives rigid & positive clamping force.
 Five stage mould close / open speed (slow-fast-slow) & pressure.
 Multi stage digital speed and pressure setting to operate the mould.
 Computer aided design toggle mechanism gives optimal mould closing and opening speed profits.
 Ramping adjustment for accurate position.
 Linear transducer for accurate clamp position.
 Mould protection with repeat again option.
 Travel time display for close & open for producing any item while operations.
 Auto-mould height adjustment with hydraulic motor.
 Hard-chrome plated high-tensile steel tie-bars with stress relieve design.
 Auto-lubrication based on shot adjustment (as standard features).
 Hydraulic ejector with multiple selection. (continuous, shake, hold etc.)
 Linear transducer on ejector cylinder.
 Shaking ejector for multi-cavity mould.
 Less vibrations & jerks due to ramp adjustment.
 Large mould mounting area for producing large articles especially useful for pet preform, pipe fittings etc.
 Platen casting design with finite element analysis for maximum rigidity.
 Mould platen with t-slots (140 Tons & above).
 Hydraulic & electrical safety interlocks during moving platen movements for moulds & operator safety.
 Separate pressure & speed setting for mould set-up.
 All casting passed through strict ultrasonic test and tensile testing process.
 High wear resistant skate-pad for heavy mould loading.
 Long life by providing oil less bushing, with graphite impregnated for toggle mechanism.
 Transparent vision on both safety doors.
 Trouble free precise clamping force for long period through heavy-duty toggle design.
 Extra life to toggle mechanism with top fixed cover which keeps clamping unit dust free.
 Mould Clamp & Fasteners


HYDRAULIC SYSTEM

Energy efficient variable displacement pump
 Digital oil temperature gauge.
 Oil level gauge (low & high).
 Direct reading hydraulic pressure.
 Contamination free oil tank with Air breather.
 Compact, easily accessible injection and clamping valves to minimize the heat generation.
 Return line filter as standard accessories.
 Alarm / shut down for return filter clogging.
 Alarm / shut down for low oil level. (hydraulic tank)
 Alarm / shut down for low lubrication oil level.
 Provides high safety as main motor shuts down on opening rear gate.
 Hydraulic directional valve on/off indicator connector.
 Inline 10 Micron Filtration unit for Oil Filling Port.

CONTROL SYSTEM

Voltage meter.
 Multi password facility for operators.
 M.C.C.B. Operating Mechanism.
 SMPS - Switched Mode Power Supply gives Linear power supply.
 Star delta motor starter for (N 100 & above).
 Digital setting timers.
 M.C.B. for each heating zone.
 PID temp controller for accurate control.
 Dedicated microprocessor control system with led input / output indicator for simplified checking
 Digital display timer.
 Digital display shot counter.
 MPCB for motor protection.
 Pressure & flow for each function control by Microprocessor.
 Linear scale for injection, clamping & ejector cylinder.
 Value change record page.
 Alarm history page.
 Printer interface with USB port.
 Production / hour in vertical-bar for year.
 In case of short circuit I/O replaceable on board.
 Easy export / import of mould & machine data.
 Hold button for on screen help (related to controller).
 Injection cool prevent time stable.
 Panel cabinet high temperature shut-down.
 Power ON time.
 Extra electric power supply socket for single phase & three phase.
 Hourly energy consumption statics page (Product cost calculator)
 Remote diagnosis by connecting with local PC via Ethernet port for any no. of machine.

Power Consumption



Note : Power Consumption is dependent on products (Articles).

SAFETY FEATURES IN RESPECT OF ALL MODELS.

Hydraulic safety on both front & rear door. | Electric mould safety.
 Magnetic grills in hopper. | Provision for M.C.C.B.
 Over load circuit breaker. | Under voltage-over voltage protection.
 Reverse phase, single phase protection.
 Providing hooks of commensurate size for risk free lifting of machine.

INJECTION UNIT

Gas nitrated hardened screw and barrel, for wear resistance and long life.

Screw for homogenous plasticizing with maddock design.

Screw back pressure with pressure gauge provision.

High torque hydraulic motor for better plasticization.

5-stage injection speed pressure & position control.

3-stage injection holding speed pressure & position control.

Hopper sliding arrangement for material removal.

Electric shot counter.

Cold slug Ejection by time.

Intrusion moulding program.

Selection of injection time & position both.

Screw tachometer (Digital RPM).

Pre-suck back function and after plasticizing suck back.

Heater failure & thermocouple failure detector.

High / low temperature alarm. (suitable low-high limit)

Auto heat start-up.

Longer life of mould with Twin Cylinder Design & Dual nozzle centering alignment device.

Linear potentiometer for injection / plasticizing.

Auto purging facility.

Ceramic bands heaters for instant heating.

Barrel heater safety cover.

Nozzle contact force confirmation with use of pressure switch.

Temperature Sensor at feed throat to ensure continuous production.

S.S. Water Manifold.

OPTIONAL FEATURES

Bi-metallic screw barrel.

Digital back pressure.

Hopper dryer & Hopper loader.

Hydraulic core-pulling and unscrewing.

Water flow regulator with temperature gauges.

Running hour-meter.

Auto-taker (robot) interface.

Air-ejector.

Hydraulic oil.

Gas injection interface only up to digital output from control.

Blowers with heaters for processing heat sensitive materials.

Nozzle shut off provision.

Hot runner temperature controller.

Extended nozzle with heater.

Multiline water battery with temperature Indicator guard.

Close loop valve.

Ladder for loading material in hopper.

Ejector in back position confirmation by proximity sensor.

Remote monitoring .

MACHINE VERSION LIST

FEATURE DESCRIPTION	V+	V++	PRO	PRO+	PRO++
CP-31/T-ECO PLC	✓	✓	✗	✗	✗
CP-33/T-Expandable PLC MODEL - 1075-0610-00	✗	✗	✓	✓	✓
En201 Safety for Clamping unit	✓	✓	✓	✓	✓
Digital Back Pressure	✗	✓	✓	✓	✓
High Speed Injection Unit	✗	✓	✓	✓	✓
High Speed Clamping Unit	✗	✗	✓	✓	✓
LM Guideways for Injection Unit	✗	✗	✓	✓	✓
LM Guideways for Clamping Unit	✗	✗	✗	✓	✓
2 Zone Hot runner output	✗	✗	✓	✗	✗
3 Zone Hot runner output	✗	✗	✗	✓	✓
Robot Interface Euromap 67	✗	✗	✓	✓	✓
Energy Meter	✗	✗	✗	✓	✓
Clamp Proportional valve for accurate mould positional accuracy	✗	✗	✗	✓	✓
Injection Proportional valve for accurate Injection Shot accuracy	✗	✗	✗	✗	✓
Water flow control valve on Heat exchanger	✗	✗	✗	✓	✓

- Photography may show attachments or accessories, which may not be part of the standard scope of supply.
- Due to continuous improvements with up-gradation of technology specification & components are subject to change without notice.



www.sumiteknatraj.com

Global Presence

Global Presence



Sumitek Natraj Machinery Private Limited

Plot No. 564, Kathwada G.I.D.C., Opp. Road.10, Nr. Tribhuvan Estate Gate, Phase-2, Kathwada, Tal-Daskroi, Ahmedabad-382430. Gujarat, India.

Website : www.sumiteknatraj.com
: www.natrajind.com

Vendor INQ : Mo.: +91- 95128 20014
Marketing : Mo.: +91- 93138 06754, 95128 20013, 75676 16655

E-mail : sales@sumiteknatraj.com | marketing@sumiteknatraj.com
: support@sumiteknatraj.com | export@sumiteknatraj.com

Service Network : Gujarat, Maharashtra, Delhi, Karnataka, Tamilnadu, Telangana, Madhya Pradesh



For Website



For PDF Brochure